COMPRESSOR DATA SHEET



Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

Manufacturer: Model Number X Air-co Lubric	: Ultima	er Denver 1 U132-125psi			
X Air-co		U132-125psi			
	oled			Date:	06/26/20
Lubric	oica	ooled Water-cooled			Screw
	cated X	Oil Free		# of Stages:	2
Full Load Operating Pressure			125	b psig	
Drive Motor Nominal Rating			88	hp	
Drive Motor Nominal Efficiency			97.0	percent	
Fan Motor Nominal Rating (if applicable)			0.48	hp	
Fan Motor Nominal Efficiency			63.0	percent	
Input Power (kW) 147.40		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d		
			762.6	20.06	
127.60			659.6	19.87	
8* 109.10			556.6	20.02	
91.80	91.80		453.6	20.61	
75.40			350.6	21.82	
60.20		. 1	247.5	24	1.59
Total Package Input Power at Zero Flow c, d			8.0	kW	
Spedic Power (KW/100 ACFM)		Note: Graph is only a vis	Capacity (ACFM) ual representation of the data in S	Section 8	800.0 900.0
	Drive Motor No Fan Motor Nor Fan Motor Nor Input Power 147.40 127.60 109.10 91.80 75.40 60.20 Total Package	Drive Motor Nominal Rating Drive Motor Nominal Effice Fan Motor Nominal Efficie Input Power (kW) 147.40 127.60 109.10 91.80 75.40 60.20 Total Package Input Power 35.00 10.00 15.00 10.00 10.00	Drive Motor Nominal Rating Drive Motor Nominal Efficiency Fan Motor Nominal Rating (if applicable) Fan Motor Nominal Efficiency Input Power (kW) 147.40 127.60 109.10 91.80 75.40 60.20 Total Package Input Power at Zero Flow c, d 35.00 30.00 Note: Graph is only a vis Note: Y-Axis Scale, 10 to 35, 40 to 25 to 35, 40 to 35, 40 to 35, 40 to 36,	Drive Motor Nominal Rating 97.0	Drive Motor Nominal Rating S8

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.2 12/19 R3